

PRODUCT DATA SHEET

Fireclamp FR Coating

DESCRIPTION	Fireclamp FR Coating is a one part, water-based and fire resistant ablative coating for use on mineral/stone wool batts to provide a complete coating or repair of previously applied coating
Applications	 On mineral/stone wool batts used to seal larger openings in fire resistant floors and walls Around the edges of service openings, for example, pipes, cables, ducts, <i>etc</i>. Finishing off or repairing pre-coated installed mineral/stone wool batts with or without service penetrations
CHARACTERISTICS AND FEATURES	 Features of Fireclamp FR Coating include: Provides up to four hours fire resistance according to BS476: Part 20: 1987 No requirement to "coat back" penetrating services Excellent adhesion to mineral/stone wool batts Easy to use, water based for quick drying and easy clean up Odourless and halogen free. White in colour Provides a smoke and gas resistant seal Specific Gravity approx. 1.40 g/cm³
DIRECTIONS FOR USE	Apply Fireclamp FR Coating around the edges of penetrating services. For un-coated batts, apply over the entire exposed surface of the batt. Cut edges of batts should be sealed with Fireclamp A Fire Resistant & Acoustic Sealant Surfaces to be sealed should be clean, dry and dust free. Apply between +5°C and +40°C. Store in cool, dry conditions at temperatures between +2°C and +30°C. Protect from frost Coverage is approximately one square metre per litre
LIMITATIONS	It is the user's responsibility to determine suitability of use. It is recommended that a sample installation be undertaken. Fireclamp FR Coating is not to be used to seal aquariums, swimming pool joints, in food contact applications or for structural glazing applications.
SAFETY	In case of contact with eyes, flush immediately with water and seek medical attention. Keep out of the reach of children. Do not ingest. For further details please refer to the Safety Data Sheet. Wear suitable protective clothing, gloves and eye and face protection Avoid contact with skin and eyes Adopt usual standards of industrial hygiene practice

Since the product is applied under circumstances beyond our control, Abesco Fire Ltd can accept no direct or consequential liability whether in contract or in tort, for the interpretations of such recommendations and reserves the right to modify the recommendations as necessary.



SHIRE HALL LOSTWITHIEL CORNWALL PL22 OBS UNITED KINGDOM T: +44 (0) 1561 377766 F: +44 (0) 1561 37888 E: sales@abesco.net W: www.abesco.net Issue date July 2016

1 of 1